



Bentonite Granular Pack

Product Description

TegraSeal Bentonite Granular Pack are bentonite clay granules used as a detail material in conjunction with the TegraSeal waterproofing membranes.

Basic Uses

TegraSeal Bentonite Granular Pack is designed for waterproofing below grade structural slabs as well as construction methods incorporating lagging, concrete caisson or shotcrete retention walls.

Packaging

30 lb. (13.6 kg) Bags

APPLICATION

Use TegraSeal Bentonite Granular Pack at the base of foundation walls, at vertical to horizontal transitions, to detail penetrations and to fill voids, and in the seams of TegraTite in horizontal applications.

For complete details, refer to TegraSeal's published architectural Guidelines or the TegraSeal website www.tegraseal.com.

INSTALLATION

Lay Granular Pack on its side, cut a 1" opening in the lower corner. Dispense a 1 ½" to 2" (38 mm to 50 mm) bentonite cant along all vertical to horizontal transitions or on horizontal seams. One 30 lb Granular Pack should cover approximately 25 to 30 linear feet.

MAINTENANCE

TegraSeal Granules requires no maintenance after installation.

LIMITED WARRANTY

TegraSeal Products, LLC (TegraSeal) warrants its products will be delivered free of defects in materials and workmanship. TegraSeal will replace the material or refund the purchase price. TegraSeal makes no other warranty, including an implied warranty of merchantability or fitness for a particular purpose. TegraSeal shall not be liable for any other loss or damage. Contact TegraSeal to discuss specific details for extended warranty periods.

TECHNICAL DATA	
Screen Analysis:	Typical
Dry Screen, 16 mesh	100%
Dry Screen, 10 mesh	1.7%
Wet Screen 200 mesh	1.3%
AFS Grain Fineness	25
Industrial Properties:	
Moisture	8.2%
Viscosity @ 600 RPM	25
Filtrate, 30 minutes @ 100 psi	18
Montmorillonite	92%