



## TegraSeal Seam Tape

### Product Description

TegraSeal Seam Tape is a 10 mil polyethylene film supporting a polyester/cotton cloth carrier with a natural rubber adhesive. TegraSeal Seam Tape provides aggressive adhesion to the joint. When used with TegraSeal waterproofing membranes, TegraSeal Seam Tape unifies the layer of HDPE waterproofing and protects the seams during backfilling.

### Basic Uses

TegraSeal Seam Tape is used for covering and protecting the seams in TegraSeal waterproofing membranes (TegraTite and TegraTite Plus).

### Installation

Examine all surfaces prior to starting application. Dust and debris must be removed. The seam should be clean and dry. Press TegraSeal Seam Tape over the seam with 1 1/2" inches on each sheet. Cover the nail holes when possible. Roll tight the TegraSeal Seam tape with a hand roller. For specific installation guidelines, please contact your TegraSeal Representative, call TegraSeal at 888-816-2168 or visit our website for details.

### Storage

Protect from moisture. Store on skid or pallet, cover with polyethylene or tarp.

### Packaging

Standard rolls are 3" x 60 yds (7.6 cm x 55 m), with 16 rolls per case.

### Availability

Available worldwide through TegraSeal distributors. Please contact us, your TegraSeal Representative, or our website for details.

### Limitations

TegraSeal Seam Tape does not provide a gas-proof barrier. Use TegraSeal Bitumen Tape for greater vapor and water barrier protection.

### Warranty

TegraSeal Products, LLC (TegraSeal) warrants its products will be delivered free of defects in materials and workmanship. TegraSeal will replace the material or refund the purchase price. TegraSeal makes no other warranty, including an implied warranty of merchantability or fitness for a particular purpose. TegraSeal shall not be liable for any other loss or damage. Contact TegraSeal to discuss specific details for extended warranty periods.

## TYPICAL PHYSICAL PROPERTIES

Physical Property	Test Method	Value
Materials		Polyethylene (10 mils) Polyester/cotton cloth Natural rubber adhesive
Adhesive Strength: to stainless steel to concrete	ASTM D1004	47 oz per inch (5.14 N/cm) 39 oz per inch (4.27 N/cm)
Tensile Strength:	ASTM D1004	27 lbs per in (47.3 N)
VOCs		Low
Installation Temperatures	ASTM D746	30°F to 200°F (-1°C to 90°C)